

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
E10000(36v) 46.10 40.60 24.30	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 4 wheel Sit down								
E10000(48v) 46.10 40.60 24.30	48 Volt:	24-85-29	1190	55.7	44.8	38.2	22.9	4656
N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 4 wheel Sit down								
E12000(36v) 46.10 40.60 24.30	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3975 Min. Weight: Term: B30 4 wheel Sit down								
E12000(48v) 46.10 40.60 24.30	48 Volt:	24-85-29	1190	55.7	44.8	38.2	22.9	4656
N/Cov. SB350Gry Connector: 3975 Min. Weight: Term: B30 4 wheel Sit down								
E20K EC20K 39.50 30.50 23.30	36 Volt:	18-85-25	1020	35.8	38.2	29.2	22.9	2988
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 Rider-Sit down								
E25K EC25K 39.50 30.50 23.30	36 Volt:	18-85-25	1020	35.8	38.2	29.2	22.9	2988
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 Rider-Sit down								
E3000(36v) E3500(36v) EC4000(36v) 35.70 27.90 23.30	36 Volt:	18-85-19	765	26.9	34.9	25.5	22.9	2340
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 wheel Sit down								
E3000(48v) E3500(48v) EC4000(48v) 35.70 27.90 23.30	48 Volt:	24-85-15	595	27.8	35.2	25.6	22.9	2568
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 wheel Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X	Y	Z	
			Ah	kWh	in. (Length)	in. (Width)	in. (Height)	
E4000 (36v) 39.50 30.50 23.30	36 Volt:	18-85-25	1020	35.8	38.2	29.2	22.9	2988
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 wheel Sit down								
E4000 (48v) 39.50 30.50 23.30	48 Volt:	24-85-19	765	35.8	38.2	29.6	22.9	3120
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 wheel Sit down								
E5000 (36v) 39.50 30.50 23.30	36 Volt:	18-85-25	1020	35.8	38.2	29.2	22.9	2988
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 4 wheel Sit down								
E5000 (48v) 39.50 30.50 23.30	48 Volt:	24-85-19	765	35.8	38.2	29.6	22.9	3120
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 4 wheel Sit down								
E7000(36v) E8000(36v) 46.10 40.60 24.30	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3400 Min. Weight: Term: B30 4 wheel Sit down								
E7000(48v) E8000(48v) 46.10 40.60 24.30	48 Volt:	24-85-29	1190	55.7	44.7	38.2	22.9	4656
N/Cov. SB350Gry Connector: 3400 Min. Weight: Term: B30 4 wheel Sit down								
EC15 (36v) 2EC15 (36v) EC18 (36v) 2EC18 (36v) 35.80 27.80 23.30	36 Volt:	18-85-17	680	23.9	33.2	25.6	22.9	2142
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 Rider-Sit down								
EC15 (48v) 2EC15 (48v) EC18 (48v) 2EC18 (48v) 35.80 27.80 23.30	48 Volt:	24-85-15	595	27.8	35.2	25.4	22.9	2568
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
EC15K(36v) EC18K(36v) EC18KL(36v) 35.70 27.90 23.30	36 Volt:	18-85-17	680	23.9	33.2	25.6	22.9	2142
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 Rider-Sit down								
EC15K(48v) EC18K(48v) EC18KL(48v) 35.70 27.90 23.30	48 Volt:	24-85-15	595	27.8	35.2	25.4	22.9	2568
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 Rider-Sit down								
EC20 (36v) 2EC20 (36v) EC25 (36v) 2EC25 (36v) 39.90 30.50 23.30	36 Volt:	18-85-25	1020	35.8	38.2	29.2	22.9	2988
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 Rider-Sit down								
EC20 (48v) 2EC20 (48v) EC25 (48v) 2EC25 (48v) 39.90 30.50 23.30	48 Volt:	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 Rider-Sit down								
EC20K(48v) 39.50 30.50 23.30	48 Volt:	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 Rider-Sit down								
EC25E (3) 2EC25E (36v) EC30 (36v) 2EC30 (36v) 39.90 34.40 23.30	36 Volt:	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 Rider-Sit down								
EC25E (48v) 2EC25E (48v) EC30 (48v) 2EC30 (48v) 39.90 34.40 23.30	48 Volt:	24-85-21	850	39.8	38.2	32.6	22.9	3408
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
EC25K(48v) 39.50 30.50 23.30	48 Volt:	24-85-19	765	35.8	38.2	29.5	22.9	3120
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 Rider-Sit down								
EC25KE EC25KL EC30K 39.50 34.40 23.30	36 Volt:	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 Rider-Sit down								
EC25KE(48v) EC25KL(48v) EC30K(48v) 39.50 34.40 23.30	48 Volt:	24-85-21	850	39.8	38.2	32.6	22.9	3408
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 Rider-Sit down								
EP 15T (36v) 39.20 20.60 24.40	36 Volt:	18-85-17	680	23.9	38.2	20.0	22.9	2142
N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: B24 Rider-Sit down								
EP 15T (48v) 39.20 20.60 24.40	48 Volt:	24-85-13	510	23.9	38.2	20.6	22.9	1222
N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: B24 Rider-Sit down								
EP 18T (36v) EP 20T (36v) 39.20 24.90 24.40	36 Volt:	18-85-21	850	29.8	38.2	24.6	22.9	2556
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: D30 Rider-Sit down								
EP 18T (48v) EP 20T (48v) 39.20 24.90 24.40	48 Volt:	24-85-15	595	27.8	38.2	23.7	22.9	2568
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: D30 Rider-Sit down								
EP16KT (36v) 40.00 20.90 24.80	36 Volt:	18-85-17	680	23.9	38.2	20.0	22.9	2142
N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B20 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
EP16KT (48v) 40.00 20.90 24.80	48 Volt:	24-85-13	510	23.9	38.2	20.6	22.9	2256
N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B20 Rider-Sit down								
EP18KT (36v) EP20KT (36v) 40.00 25.00 24.80	36 Volt:	18-85-21	850	29.8	38.2	24.6	22.9	2556
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 Rider-Sit down								
EP18KT (48v) EP20KT (48v) 40.00 25.00 24.80	48 Volt:	24-85-15	595	27.8	38.2	23.7	22.9	2568
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 Rider-Sit down								
ET3000 (36v) 40.00 20.90 24.80	36 Volt:	18-85-17	680	23.9	38.2	20.0	22.9	2142
N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B24 Rider-3 wheel								
ET3000 (48v) 40.00 20.90 24.80	48 Volt:	24-85-13	510	23.9	38.2	20.6	22.9	2256
N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B24 Rider-3 wheel								
ET3500 (36v) ET4000 (36v) 40.00 24.90 24.80	36 Volt:	18-85-21	850	29.8	38.2	24.6	22.9	2556
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 Rider-3 wheel								
ET3500 (48v) ET4000 (48v) 40.00 24.90 24.80	48 Volt:	24-85-15	595	27.8	38.2	23.7	22.9	2568
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 Rider-3 wheel								
EX5000 (36v) E5500 (36v) E6000 (36v) E6500 (36v) 39.50 34.40 23.30	36 Volt:	18-85-29	1190	41.8	38.2	33.7	22.9	3492
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 wheel Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
EX5000 (48v) E5500 (48v) E6000 (48v) E6500 (48v) 39.50 34.40 23.30	48 Volt:	24-85-21	850	39.8	38.2	32.7	22.9	3408
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 wheel Sit down								
F25 (36v) F30 (36v) 39.50 20.60 24.40	36 Volt:	18-85-17	680	23.9	38.2	20.0	22.9	2142
N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: D30 Rider-Sit down								
F25 (48v) F30 (48v) 39.50 20.60 24.40	48 Volt:	24-85-13	510					Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: D30 Rider-Sit down								
F35 (36v) F40 (36v) 39.60 24.90 24.40	36 Volt:	18-85-21	850	29.8	38.2	24.6	22.9	2556
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: D30 Rider-Sit down								
F35 (48v) F40 (48v) 39.60 24.90 24.40	48 Volt:	24-85-15	595	27.8	38.2	23.6	22.9	2568
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: D30 Rider-Sit down								
F40D (36v/18") F50D (36v/18") 45.50 41.30 18.90	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: D30 Rider-Sit down								
F40D (36v/20") F50D (36v/20") 45.50 41.30 20.90	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 2425 Min. Weight: Term: D30 Rider-Sit down								
F40D (48v/18") F50D (48v/18") 45.50 41.30 18.90	48 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: D30 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
F40D (48v/20") F50D (48v/20") 45.50 41.30 20.90	48 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 2425 Min. Weight: Term: D30 Rider-Sit down								
F40DSA (36v) 45.50 41.30 23.00	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 2425 Min. Weight: Term: D30 Rider-Sit down								
F40DSA (48v) 45.50 41.30 23.00	48 Volt:	24-85-29	1190	55.7	44.8	38.2	22.9	4656
N/Cov. SB350Gry Connector: 2425 Min. Weight: Term: D30 Rider-Sit down								
F50D (36v/24") 45.50 41.30 24.10	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 2425 Min. Weight: Term: D30 Rider-Sit down								
F50D (48v/24") 45.50 41.30 24.10	48 Volt:	24-85-29	1190	55.7	44.8	38.2	22.9	4656
N/Cov. SB350Gry Connector: 2425 Min. Weight: Term: D30 Rider-Sit down								
F50DSA (36v) 45.50 41.30 23.00	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3250 Min. Weight: Term: D30 Rider-Sit down								
F50DSA (48v) 45.50 41.30 23.00	48 Volt:	24-85-29	1190	55.7	44.8	38.2	22.9	4656
N/Cov. SB350Gry Connector: 3250 Min. Weight: Term: D30 Rider-Sit down								
F60D (36v/18") 45.60 49.30 18.90	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: D30 Rider-Sit down								
F60D (36v/20") 45.60 49.30 20.90	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: D30 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
F60D (36v/24") 45.60 49.30 24.10	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3350 Min. Weight: Term: D30 Rider-Sit down								
Call for more info:(630) 851-5800								
F60D (48v/18") 45.60 49.30 18.90	48 Volt:							
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: D30 Rider-Sit down								
F60D (48v/20") 45.60 49.30 20.90	48 Volt:							
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: D30 Rider-Sit down								
F60D (48v/24") 45.60 49.30 24.10	48 Volt:							
N/Cov. SB350Gry Connector: 3350 Min. Weight: Term: D30 Rider-Sit down								
Call for more info:(630) 851-5800								
F60DSA (36v) 45.50 49.20 23.00	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3350 Min. Weight: Term: D30 Rider-Sit down								
F60DSA (48v) 45.50 49.20 23.00	48 Volt:	24-85-29	1190	55.7	44.8	38.2	22.9	4656
N/Cov. SB350Gry Connector: 3350 Min. Weight: Term: D30 Rider-Sit down								
M025 (36v) M030 (36v) M035D (36v) 34.50 28.00 24.13	36 Volt:	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350Gry Connector: 1800 Min. Weight: Term: B18 Rider-Sit down								
M025 (48v) M030 (48v) M035D (48v) 34.50 28.00 24.13	48 Volt:	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Gry Connector: 1800 Min. Weight: Term: B18 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
M040D (36v) M040DSA (36v) 40.20 30.50 23.60	36 Volt:	18-85-25	1020	35.8	38.2	29.1	22.9	2988
N/Cov. SB350Gry Connector: 2400 Min. Weight: Term: B18 Rider-Sit down								
M040D (48v) M040DSA (48v) 40.20 30.50 23.60	48 Volt:	24-85-19	765	35.8	38.1	29.5	22.9	3120
N/Cov. SB350Gry Connector: 2400 Min. Weight: Term: B18 Rider-Sit down								
M050D (36v) M050DSA (36v) 40.20 33.30 23.60	36 Volt:	18-85-27	1105	38.8	38.2	31.4	22.9	3240
N/Cov. SB350Gry Connector: 2950 Min. Weight: Term: B18 Rider-Sit down								
M050D (48v) M050DSA (48v) 40.20 33.30 23.60	48 Volt:	24-85-21	850	39.8	38.2	32.6	22.9	3408
N/Cov. SB350Gry Connector: 2950 Min. Weight: Term: B18 Rider-Sit down								
M050DSA (36v/low profile) 40.20 36.40 20.67	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 0 Min. Weight: Term: B18 Rider-Sit down								
M060DSA (36v) 40.20 34.40 23.60	36 Volt:							Call for more info:(630) 851-5800
N/Cov. SB350Gry Connector: 3060 Min. Weight: Term: B18 Rider-Sit down								
M060DSA (48v) 40.20 34.40 23.60	48 Volt:	24-85-21	850	39.8	38.2	32.6	22.9	3408
N/Cov. SB350Gry Connector: 3060 Min. Weight: Term: B18 Rider-Sit down								
M070D 36v) M080D (36v) 43.30 40.50 24.00	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 Rider-Sit down								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
M070D(48v) M080D (48v) 43.30 40.50 24.00	48 Volt:	24-85-27	1105	51.7	42.0	38.5	22.9	4320
N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 Rider-Sit down								
M100D(36v) M120D (36v) 43.30 40.50 24.00	36 Volt:	18-85-33	1360	47.7	38.4	38.2	22.9	4032
N/Cov. SB350Gry Connector: 4000 Min. Weight: Term: B30 Rider-Sit down								
M100D(48v) M120D (48v) 43.30 40.50 24.00	48 Volt:	24-85-27	1105	51.7	42.0	38.5	22.9	4320
N/Cov. SB350Gry Connector: 4000 Min. Weight: Term: B30 Rider-Sit down								
MC40D (36v) 34.50 28.00 24.13	36 Volt:	18-85-17	680	23.9	33.1	25.6	22.9	2142
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B18 Rider-Sit down								
MC40D (48v) 34.50 28.00 24.13	48 Volt:	24-85-13	510	23.9	30.6	25.4	22.9	2256
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B18 Rider-Sit down								
2 CLASS: 2 CLASS: 2 CLASS:								
EC15KS (13") EC18KS (13") 38.50 13.60 32.30	36 Volt:	18-125-11	625	21.9	38.2	13.1	30.3	1890
N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: C16 Stand-up end control								
EC15KS (16") EC18KS (16") 38.50 16.25 32.30	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C16 Stand-up end control								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
EC15KS (18") EC18KS (18") 38.50 18.50 32.30	36 Volt:	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: C16 Stand-up end control								
EC15KS (21") EC18KS (21") 38.50 21.25 32.30	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C16 Stand-up end control								
EC20KS (36/18") 38.50 18.50 32.30	36 Volt:	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: C16 Stand-up end control								
EC20KS (36/21") 38.50 21.25 32.30	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: C16 Stand-up end control								
EC25KS 38.50 23.75 32.30	36 Volt:	18-125-19	1125	39.5	38.2	22.3	30.3	3204
N/Cov. SB350Gry Connector: 2700 Min. Weight: Term: C16 Stand-up end control								
ND2500(24v) 38.58 14.25 31.65	24 Volt:	12-125-17	1000	23.4	38.1	13.0	30.3	1896
N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B24 Reach								
ND2500(36v/14") NR3000(36v/14") NS3000(36v/14") 38.58 14.25 31.65	36 Volt:	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B24 Reach								
ND3000 (36v/18") ND3000P (36v/18") 38.58 18.25 31.65	36 Volt:	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
ND3000P (36v/21") 38.58 21.25 31.65	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 Reach								
ND3000P(36v/16") ND2500(36v/16") ND3000(36v/16") 38.58 16.25 31.65	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								
NOR 22 32.80 13.50 32.00	24 Volt:	12-125-13	750	17.6	30.6	12.8	30.3	1500
N/Cov. SB175Red Connector: 950 Min. Weight: Term: A12 Order Picker-low								
NOR 30 31.00 13.00 30.88	24 Volt:	12-125-13	750	17.6	30.6	12.8	30.3	1500
N/Cov. SB350Red Connector: 950 Min. Weight: Term: C20 Order Picker-low								
NOR 30(36"L) 36.75 14.50 32.25	24 Volt:	12-125-13	750	17.6	36.0	14.0	30.3	1500
N/Cov. SB350Red Connector: 920 Min. Weight: Term: C20 Order Picker-low								
NOR 30P (24v) 36.88 14.00 30.88	24 Volt:	12-125-15	875	20.5	35.1	12.9	30.3	1692
N/Cov. SB350Red Connector: 1600 Min. Weight: Term: C20 Order picker								
NOR 30P (36v) 38.88 14.00 30.88	36 Volt:	18-125-11	625	21.9	38.1	13.1	30.3	1890
N/Cov. SB350Red Connector: 1600 Min. Weight: Term: C20 Order picker								
NR3000 (36v/16") NR3500 (36v/16") 38.58 16.25 31.65	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
NR3000(24v) NR3500(24v) NR4000(24v) 38.58 14.25 31.65	24 Volt:	12-125-17	1000	23.4	38.0	13.5	30.3	1896
N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B24 Reach								
NR3500(36v/18") NR4000(36v/18") NR4500(36v/18") 38.58 18.25 31.65	36 Volt:	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								
NR4000P(36v/16") NR4500P(36v/16") NR4000(36v/16") NR4500(36v/16") 38.58 16.25 31.65	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								
NR4000P(36v/18") NR4500P(36v/18") 38.58 18.25 31.65	36 Volt:	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								
NR4000P(36v/21") NR4500P(36v/21") NR4000(36v21") NR4500(36v/21") 38.58 21.25 31.65	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 Reach								
NRR30 NRR35 NRR40 38.67 14.25 31.62	24 Volt:	12-125-17	1000	23.4	38.0	13.5	30.3	1896
N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B11 Reach								
NRR30P (21") NRR40P (21") NRR35P (21") NRR45P (21") 38.67 21.25 31.62	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B11 Reach								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
NRR40 (16") NRR30 (16") NRR35 (16") 38.67 16.25 31.62	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach								
NRR40P (16") NRR30P (16") NRR45P (16") NRR35P (16") 38.67 16.25 31.62	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach								
NS3000 (36v/16") NS4000 (36v/16") 38.58 16.25 31.65	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								
NS3000(24v) NS4000(24v) 38.58 14.25 31.65	24 Volt:	12-125-17	1000	23.4	38.0	13.5	30.3	1896
N/Cov. SB350Gry Connector: 1700 Min. Weight: Term: B24 Reach								
NS4000 (36v/18") 38.58 18.25 31.65	36 Volt:	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 Reach								
NSR30 (14") NSR40 (14") 38.67 14.25 31.62	24 Volt:	12-125-17	1000	23.4	38.0	13.5	30.3	1896
N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B11 Straddle truck								
NSR30 (16") NSR40 (16") 38.67 16.25 31.62	24 Volt:	12-125-19	1125	26.3	38.2	14.8	30.3	2136
N/Cov. SB350Red Connector: 2000 Min. Weight: Term: B11 Straddle truck								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
NSR30P (16") NSR40P (16") 38.67 16.25 31.62	36 Volt:	18-125-13	750	38.0	38.1	15.4	30.3	1625
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Straddle truck								
NSR30P (21") NSR40P (21") 38.67 21.25 31.62	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B11 Straddle truck								
Class 3								
NDC100 31.50 13.44 24.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Gry Connector: 825 Min. Weight: Term: B18 Tow tractor								
NPC 80 31.50 13.44 24.00	24 Volt:	12-125-13	750	17.6	30.6	12.8	30.3	1500
W/Cover SB175Gry Connector: 825 Min. Weight: Term: B18 Pallet-Rider/Walkie								
NPP 40 28.12 8.88 26.50	24 Volt:	12-100-7	300	7.0	25.3	Call for more info:(630) 851-5800		
W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie								
NPP 40 (opt) 29.38 8.88 26.50	24 Volt:	12-100-7	300	7.0	25.3	Call for more info:(630) 851-5800		
W/Cover SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie								
NPP60 (13") 32.00 13.44 24.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Gry Connector: 575 Min. Weight: Term: B18 Pallet-Rider/Walkie								
NPP60 (9") 32.00 9.19 24.00	24 Volt:	12-85-7	255	6.0	Call for more info:(630) 851-5800			
W/Cover SB175Gry Connector: 575 Min. Weight: Term: B18 Pallet-Walkie								

CAT FORKLIFT MODEL BATTERY COMPARTMENT SIZE (Inches)	V O L T	BATTERY TYE	CAPACITY		BATTERY DIMENSIONS			Approx. BATTERY WEIGHT (Lbs.)
			6 HOUR RATE		X in. (Length)	Y in. (Width)	Z in. (Height)	
			Ah	kWh				
NPS60 NPV60 NPC60 (13") 32.00 13.44 24.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Gry Connector: 825 Min. Weight: Term: B18 Pallet-Rider/Walkie								
NPV80 NPS80 31.50 13.44 24.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Gry Connector: 825 Min. Weight: Term: B18 Pallet-Rider/Walkie								
NRDR25 NRDR30 38.67 14.25 31.62	24 Volt:	12-125-17	23.4		38.0	13.0	30.3	1896
W/Cover SB350Red Connector: 1600 Min. Weight: Term: 00 Pallet-Rider/Walkie								
NRDR25P (21") NRDR30P (21") 38.67 21.25 31.62	36 Volt:	18-125-17	1000	35.1	38.1	20.1	30.3	2844
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B11 Pallet-Rider/Walkie								
NRDR30P (16") NRDR25P (16") NRDR30 (16") NRDR25 (16") 38.67 16.25 31.62	36 Volt:	18-125-13	750	26.3	38.1	15.4	30.3	2250
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Pallet-Rider/Walkie								
NRP30 NSP30 NSP40 31.90 13.40 24.00	24 Volt:	12-85-13	510	11.9	30.6	12.8	23.3	1128
W/Cover SB175Gry Connector: 975 Min. Weight: Term: B18 Pallet-Stacker/Walkie								
SS3000 SS3500 28.20 11.00 23.60	24 Volt:	12-85-7	255	6.0	25.3	8.6	23.3	588
N/Cov. SB175Gry Connector: 510 Min. Weight: Term: A12 Pallet-Straddle								

