

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
Battery Compartment Size			Ah	kWh					
Class 1 Trucks									
FB13M-2 36.60 17.10 24.00	24 V	12-85-15	595	13.9	35.1	12.9	22.9	1284	
N/Cov. connector option 0 Min. Weight: Connector option 3 wheel sit down Trk dims:									
FB15M-2 (24v) FB18M-2 (24v) FB15MK-2 (24v) FB18MK-2 (24v) 39.20 20.60 24.00	24 V	12-85-25	1020	23.9	38.2	19.5	22.9	1992	
N/Cov. connector option 1565 Min. Weight: Connector option 3 wheel sit down Trk dims:									
FB15M-2 (36v) FB18M-2 (36v) FB15MK-2 (36v) FB18MK-2 (36v) 39.20 20.60 24.00	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142	
N/Cov. connector option 1565 Min. Weight: Connector option 3 wheel sit down Trk dims:									
FB15M-3 (36v) FB18M-3 (36v) 38.80 20.60 24.00	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142	
N/Cov SB350Gry Connector: 1570 Min. Weight: Term: B14 3 wheel sit down Trk dims:									
FB15M-3 (48v) FB18M-3 (48v) 38.80 20.60 24.00	48 V	24-85-13	510	26.1	38.2	20.6	22.9	2256	
N/Cov SB350Gry Connector: 1570 Min. Weight: Term: B14 3 wheel sit down Trk dims:									
FB15SH-6 (36v) FB18SH-6 (36v) 36.20 27.00 23.70	36 V	18-85-19	765	26.9	35.9	25.6	22.9	2340	
N/Cov SB350Gry Connector: 1940 Min. Weight: Term: B14 4wheel sit down Trk dims:									
FB15SH-6 (48v) FB18SH-6 (48v) 36.20 27.00 23.70	48 V	24-85-15	595	27.8	35.2	25.4	22.9	2568	
N/Cov SB350Gry Connector: 1940 Min. Weight: Term: B14 4wheel sit down Trk dims:									
FB15SH-7 (36v)	36 V	18-85-19	765	26.9	35.9	25.6	22.9	2340	

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FB18SH-7 (36v) 36.20 27.00 24.20									
N/Cov SB350Gry Connector: 1940 Min. Weight: Term: B14 4wheel sit down Trk dims:									
FB15SH-7 (48v) 36.20 27.00 24.20	48 V	24-85-15	595	27.8	35.2	25.4	22.9	2568	
FB18SH-7 (48v) 36.20 27.00 24.20									
N/Cov SB350Gry Connector: 1940 Min. Weight: Term: B14 4wheel sit down Trk dims:									
FB15SHE-7 (36v) 36.20 27.00 24.20	36 V	18-85-19	765	26.9	35.9	25.6	22.9	2340	
FB18SHE-7 (36v) 36.20 27.00 24.20									
N/Cov SB350Gry Connector: 1940 Min. Weight: Term: B14 4wheel sit down									
FB15SHE-7 (48v) 36.20 27.00 24.20	48 V	24-85-15	595	27.8	35.2	25.4	22.9	2568	
FB18SHE-7 (48v) 36.20 27.00 24.20									
N/Cov SB350Gry Connector: 1940 Min. Weight: Term: B14 4wheel sit down									
FB16iX-1 40.94 22.83 31.02	80 V	40-125-7	375	29.3	Call for more information: (630) 851-5800				
FB18iX-1 40.94 22.83 31.02									
FB20iX-1(22") 40.94 22.83 31.02									
N/Cov. connector option 2587 Min. Weight: Connector option 4wheel sit down									
FB16X-1 40.94 22.83 31.02	80 V	40-125-7	375		Call for more information: (630) 851-5800				
FB18X-1 40.94 22.83 31.02									
FB20X-1(22") 40.94 22.83 31.02									
N/Cov. connector option 2587 Min. Weight: Connector option 4wheel sit down									
FB18MG-3 (36v) 39.00 25.00 24.00	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556	
FB20M-3(36v) 39.00 25.00 24.00									
N/Cov SB350Gry Connector: 2160 Min. Weight: Term: B14 3 wheel sit down									
FB18MG-3 (48v) 39.00 25.00 24.00	48 V	24-85-15	595	27.8	38.1	23.6	22.9	2568	
FB20M-3(48v) 39.00 25.00 24.00									
N/Cov SB350Gry Connector: 2160 Min. Weight: Term: B14 3 wheel sit down									
FB20iX-1(28") 40.94 22.83 31.02	80 V	40-125-9	500	39	Call for more information: (630) 851-5800				
FB22iX-1									

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FB25iX-1 40.94 28.43 31.22									
N/Cov. connector option 2458 Min. Weight: Connector option 4wheel sit down									
FB20S-5 (36V) 39.20 28.00 24.00	36 V	18-85-23	935	32.8	38.1	26.9	22.9	2736	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20S-5 (48V) 39.20 28.00 24.00	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20SH-4 (36v) FB25SH-4 (36v) 39.20 28.00 23.60	36 V	18-85-23	935	32.8	38.2	26.9	22.9	2736	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B14 4wheel sit down Trk dims:									
FB20SH-4 (48v) FB25SH-4 (48v) 39.20 28.00 23.60	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B14 4wheel sit down Trk dims:									
FB20SH-5 (36V,28") 39.20 28.00 24.00	36 V	18-85-23	935	32.8	38.2	26.9	22.9	2736	
N/Cov. connector option 2300 Min. Weight: Connector option 4wheel sit down Trk dims:									
FB20SH-5 (48V,28") 39.20 28.00 24.00	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20SH-6 (36V) FB25SH-6 (36V) 38.80 29.10 23.80	36 V	18-85-23	935	32.8	38.2	26.9	22.9	2736	
N/Cov SB350Gry Connector: 2430 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20SH-6 (48V) FB25SH-6 (48V)	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856	

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FB30SH-6 (36v) 38.80 36.20 23.80									
N/Cov SB350Gry Connector: 3000 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20SHG-6 (48v) FB25SHG-6 (48v) FB30SH-6 (48v) 38.80 36.20 23.80	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov SB350Gry Connector: 3000 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20SHGE-5 (36V) FB25SHHGE-5(36V) FB30SHE-5(36V) 39.20 33.40 24.00	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240	
N/Cov SB350Gry Connector: 3000 Min. Weight: Term: B18 4wheel sit down									
FB20SHGE-5 (48V) FB25SHHGE-5(48V) FB30SHE-5(48V) 39.20 33.40 24.00	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov SB350Gry Connector: 3000 Min. Weight: Term: B18 4wheel sit down									
FB20SHH-5 (36V) FB25SHH-5 (36V) 39.20 28.00 24.00	36 V	18-85-23	935	32.8	38.2	26.9	22.9	2736	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20SHH-5 (48V) FB25SHH-5 (48V) 39.20 28.00 24.00	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB20X-1(28") FB22X-1 FB25X-1 40.94 28.43 31.22	80 V	40-125-9	500	39	Call for more information: (630) 851-5800				
N/Cov. connector option 2458 Min. Weight: Connector option 4wheel sit down									
FB25LiX-1 FB30iX-1 40.94 34.06 31.22	80 V	40-125-11	625	48.8	Call for more information: (630) 851-5800				
N/Cov. connector option 2458 Min. Weight: Connector option 4wheel sit down									

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FB25LX-1 FB30X-1 FB35X-1 40.94 34.06 31.22	80 V	40-125-11	625	48.8	Call for more information: (630) 851-5800				
N/Cov. connector option 2458 Min. Weight: Connector option 4wheel sit down									
FB25S-5 (36V) 39.20 28.00 24.00	36 V	18-85-23	935	32.8	38.2	26.9	22.9	2736	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB25S-5 (48V) 39.20 28.00 24.00	48 V	24-85-17	680	38.29	38.1	26.9	22.9	2856	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB25SH-5 (36V,28") 39.20 28.00 24.00	36 V	18-85-23	935	32.8	38.2	26.9	22.9	2736	
N/Cov. connector option 2300 Min. Weight: Connector option 4wheel sit down Trk dims:									
FB25SH-5 (48V,28") 39.20 28.00 24.00	48 V	24-85-17	680	31.8	38.1	26.9	22.9	2856	
N/Cov SB350Gry Connector: 2300 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB25SHG-5 (36V,33") 39.20 33.40 24.00	36 V	18-85-27	1105	38.8	38.2	31.4	22.9	3240	
N/Cov. connector option 3000 Min. Weight: Connector option 4wheel sit down Trk dims:									
FB25SHG-5 (48V,33") 39.20 33.40 24.00	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. connector option 3000 Min. Weight: Connector option 4wheel sit down Trk dims:									
FB25SHHG-5 (36V) FB30SHH-5 (36V) 39.20 33.40 24.00	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240	
N/Cov SB350Gry Connector: 3000 Min. Weight: Term: B18 4wheel sit down Trk dims:									
FB25SHHG-5 (48V) FB30SHH-5 (48V) 39.20 33.40 24.00	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov SB350Gry Connector: 3000 Min. Weight: Term: B18 4wheel sit down Trk dims:									

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
FB30SH-5 (36V,33") 39.20 33.40 24.00	36 V	18-85-27	1105	38.8	38.1	31.4	22.9	3240
N/Cov. connector option 3000 Min. Weight: Connector option 4wheel sit down Trk dims:								
FB30SH-5 (48V,33") 39.20 33.40 24.00	48 V	24-85-21	850	35.1	38.1	32.6	22.9	3408
N/Cov. connector option 3000 Min. Weight: Connector option 4wheel sit down Trk dims:								
FB32SH-6 (36v) 38.80 36.20 23.80	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	3492
N/Cov SB350Gry Connector: 3300 Min. Weight: Term: B18 4wheel sit down Trk dims:								
FB32SH-6 (48v) 38.80 36.20 23.80	48 V							Call for more information: (630) 851-5800
N/Cov SB350Gry Connector: 3300 Min. Weight: Term: B18 4wheel sit down Trk dims:								
FB35SH-1 (36V) 44.60 39.60 24.00	36 V							Call for more information: (630) 851-5800
N/Cov SB350Gry Connector: 3585 Min. Weight: Term: B18 4wheel sit down Trk dims:								
FB35SH-1 (48V) 44.60 39.60 24.00	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
N/Cov SB350Gry Connector: 3585 Min. Weight: Term: B18 4wheel sit down Trk dims:								
FB35ZSH-1 (36V) 44.60 39.60 24.00	36 V	18-85-33	1360	47.7	38.3	38.1	22.9	4032
N/Cov SB350Gry Connector: 3491 Min. Weight: Term: B18 4wheel sit down Trk dims:								
FB35ZSH-1 (48V) 44.60 39.60 24.00	48 V	24-85-27	1105	51.7	42	38.5	22.9	4320
N/Cov SB350Gry Connector: 3491 Min. Weight: Term: B18 4wheel sit down Trk dims:								
FB40X-1 FB45X-1 FB50X-1 40.63 39.88 31.22	80 V	40-125-13	750	35.1				Call for more information: (630) 851-5800
N/Cov. connector option 4552 Min. Weight: Connector option 4wheel sit down								

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
------------------------	------------------	----------------	--------------------------------------	--	----------------------------	---	--	--	--------------------------------------

FB45SH-1 (36V) 36 V Call for more information: (630) 851-5800
44.60 39.60 24.00

N/Cov SB350Gry Connector: 3450 Min. Weight: Term: B18 4wheel sit down Trk dims:

FB45SH-1 (48V) 48 V 24-85-27 1105 51.7 42 38.5 22.9 4320
44.60 39.60 24.00

N/Cov SB350Gry Connector: 3450 Min. Weight: Term: B18 4wheel sit down Trk dims:

FB45SHG-1 (36V) 36 V Call for more information: (630) 851-5800
44.60 43.10 24.00

N/Cov SB350Gry Connector: 3450 Min. Weight: Term: B18 4wheel sit down Trk dims:

FB45SHG-1 (48V) 48 V Call for more information: (630) 851-5800
44.60 43.10 24.00

N/Cov SB350Gry Connector: 3450 Min. Weight: Term: B18 4wheel sit down Trk dims:

FB55SH-1 (36V) 36 V Call for more information: (630) 851-5800
FB55SHG-1 (36V)
44.60 39.60 24.00

N/Cov SB350Gry Connector: 4250 Min. Weight: Term: B18 4wheel sit down Trk dims:

FB55SH-1 (48V) 48 V 24-85-27 1105 51.7 42 38.5 22.9 4320
FB55SHG-1 (48V)
44.60 39.60 24.00

N/Cov SB350Gry Connector: 4250 Min. Weight: Term: B18 4wheel sit down Trk dims:

2 CLASS: 2 CLASS: 2 CLASS:

FR 23S-2A (20") 36 V 18-125-17 1000 35.1 38.1 20.1 30.3 2844
FR15DR-2A (20")
38.75 20.90 32.00

N/Cov SB350Gry Connector: 2400 Min. Weight: Term: C15 Reach Trk dims:

FR15S-1A (36/14") 36 V 18-125-11 625 21.9 38.1 13.2 30.3 1890
FR20S-1A (36/14")
FR23S-1A (36/14")
38.75 14.50 32.00

N/Cov SB350Gry Connector: 0 Min. Weight: Term: B20 Reach Trk dims:

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
Battery Compartment Size			Ah	kWh					
FR18S-2A (24/14") 38.75 14.40 32.00	24 V	12-125-17	1000	23.4	38	13	30.3	1896	
N/Cov SB350Gry Connector: 1600 Min. Weight: Term: C15 Reach									
FR18S-2A (24/16") 38.75 16.40 32.00	24 V	12-125-19	1125	26.3	38.2	14.8	30.3	2136	
N/Cov SB350Gry Connector: 2000 Min. Weight: Term: C15 Reach Trk dims:									
FR18S-2A (36/14") 38.75 14.40 32.00	36 V	18-125-11	625	21.9	38.1	13.2	30.3	1890	
N/Cov SB350Gry Connector: 1600 Min. Weight: Term: C15 Reach									
FR18S-2A (36/16") FR15DR-2A (16") FR23S-2A (16") 38.75 16.40 32.00	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov SB350Gry Connector: 2000 Min. Weight: Term: C15 Reach Trk dims:									
FR20S-1A (24/14") FR23S-1A (24/14") FR15S-1A (24/14") 38.75 14.50 32.00	24 V	12-125-17	1000	23.4	38.1	13	30.3	1896	
N/Cov SB350Gry Connector: 0 Min. Weight: Term: B20 Reach Trk dims:									
FR23S-1A (36/16") FR20S-1A (36/16") FR15S-1A (36/16") 38.75 16.50 32.00	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov SB350Gry Connector: 0 Min. Weight: Term: B20 Reach Trk dims:									
FR23S-1A (36/21") 38.75 21.00 32.00	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov SB350Gry Connector: 0 Min. Weight: Term: B20 Reach Trk dims:									
FS15S-1 (36/16") FS18S-1 (36/16") FS15SH-1 (36/16") FS18SH-1 (36/16") 38.70 16.10 31.50	36 V	18-125-13	750	26.3	38.1	15.4	30.3	2250	
N/Cov SB350Gry Connector: 1925 Min. Weight: Connector option Rider-Stand up Trk dims:									

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
Battery Compartment Size			Ah	kWh					
FS17SH-1 (36/18") FS19SH-1 (36/18") 38.80 18.10 31.50	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov SB350Gry Connector: 2175 Min. Weight: Connector option Rider-Stand up Trk dims:									
FS20S-1 (36/20") FS20SH-1 (36/20") FS23SH-1 (36/20") FS25SH-1 (36/20") FS28SH-1 (36/20") 38.80 20.70 31.50	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov SB350Gry Connector: 2700 Min. Weight: Connector option Rider-Stand up Trk dims:									
FS30SH-1 (36/20") FSV13SH-1 (36/20") 38.80 20.70 31.50	36 V								Call for more information: (630) 851-5800
N/Cov SB350Gry Connector: 2800 Min. Weight: Connector option Rider-Stand up									
MPF07-1A (24v) 32.00 13.50 25.50	24 V	12-85-13	510	11.9	30.6	12.8	22.9	1128	
N/Cov SB350Gry Connector: 0 Min. Weight: Term: B18 Order picker Trk dims:									
MPF07-1A (12v) 32.00 8.00 25.50	12 V	6-85-13			30.6	7.8	23.3	564	
N/Cov SB350Gry Connector: 0 Min. Weight: Term: B18 Order picker Trk dims:									
MPF15-1A (24v) 36.25 13.88 31.50	24 V	12-125-15	875	20.5	35.1	12.9	30.3	1692	
N/Cov SB350Gry Connector: 1600 Min. Weight: Term: B18 Order picker									
MPF15-1A (36v) 38.25 13.88 31.50	36 V	18-125-11	625	21.9	38.1	13.2	30.3	1890	
N/Cov SB350Gry Connector: 1600 Min. Weight: Term: B18 Order picker									
MPF15-2A 38.25 13.88 31.50	24 V	12-125-15	875	20.5	38	12	30.3	1692	
N/Cov 322-SB350Red Connector: 1500 Min. Weight: Term: C18 Order picker Trk dims:									
Class 3 Trucks									
MWE31-1A (13") MWE36-1A (13")	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	

KOMATSU Forklift Model	V	BATTERY	CAPACITY		BATTERY	DIMENSIONS			TOTAL
Battery	O	TYE	6 HOUR		X	Y	Z	BATTERY	
Compartment Size	L		Ah	kWh	in.	in.	in.	WEIGHT	
	T				(L)	(W)	(H)	(Lbs.)	

31.70 13.31 40.00

W/Cover SB175Red Connector: 400 Min. Weight: Term: B15 Pallet truck Trk dims:

MWE31-1A (8") 24 V 12-85-5 170 25.31 Call for more information: (630) 851-5800
MWE36-1A (8")
31.75 8.13 40.00

W/Cover SB175Red Connector: 400 Min. Weight: Term: B15 Pallet truck Trk dims:

MWH 15-1A 24 V 12-100-13 600 14 Call for more information: (630) 851-5800
32.30 13.30 40.00

W/Cover SB175Red Connector: 980 Min. Weight: Term: B20 Pallet truck

MWH10C-1A 24 V 12-100-13 600 14 Call for more information: (630) 851-5800
MWH15C-1A
32.30 13.30 40.00

W/Cover SB175Red Connector: 980 Min. Weight: Term: B20 Pallet truck

MWH15-1A 24 V 12-100-13 600 14 Call for more information: (630) 851-5800
MWH20-1A
MWH15R-1A
MWH20C-1A
32.30 13.30 40.00

W/Cover SB175Red Connector: 980 Min. Weight: Term: B20 Pallet truck

MWL22-1A (28L") 24 V 12-85-7 255 6 25.4 8.7 23.3 708
28.25 9.00 24.00

W/Cover SB175Red Connector: 350 Min. Weight: Term: B18 Pallet jacks Trk dims:

MWL22-1A (31L") 24 V 12-85-7 255 6 25.4 8.7 23.3 708
31.25 9.00 24.00

W/Cover SB175Red Connector: 350 Min. Weight: Term: B18 Pallet jacks

MWL22-2A (28L") 24 V 12-85-7 255 6 25.4 8.7 23.3 708
28.25 9.00 24.00

W/Cover SB175Red Connector: 350 Min. Weight: Term: B18 Pallet jacks Trk dims:

MWL22-2A (31L") 24 V 12-85-7 255 6 25.4 8.7 23.3 708
31.25 9.00 24.00

KOMATSU Forklift Model	V O L T	BATTERY TYE	CAPACITY 6 HOUR RATE		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
W/Cover SB175Red Connector: 350 Min. Weight: Term: B18 Pallet jacks									
MWL25-1A (12/13") 31.70 13.31 40.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564	
W/Cover SB175Red Connector: 400 Min. Weight: Term: B15 Pallet truck									
MWL25-1A (12/8") 31.70 8.13 40.00	12 V	6-85-13	510	6	30.6	7.8	23.3	564	
W/Cover SB175Red Connector: 400 Min. Weight: Term: B15 Pallet truck Trk dims:									
MWL31-1A (8") MWL36-1A (8") 31.70 8.13 40.00	24 V	12-85-5	170	4	Call for more information: (630) 851-5800				
W/Cover SB175Red Connector: 400 Min. Weight: Term: B15 Pallet truck Trk dims:									
MWL36-1A (24/13") MWL31-1A (13") 31.70 13.31 40.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cover SB175Red Connector: 400 Min. Weight: Term: B15 Pallet truck Trk dims:									