

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh	BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
---	------------------	-----------------	--------------------------------------	----------------------------	-------------------------------	-----------------	--------------------------------------

Class 1 Trucks

2FBC15(36v) 36 V 18-85-19 765 26.9 34.9 25.5 22.9 2340
 2FBC18(36v)
 35.80 27.80 23.30

N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down

2FBC15(48v) 48 V 24-85-15 595 27.8 35.2 25.4 22.9 2568
 2FBC18(48v)
 35.80 27.80 23.30

N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down

2FBC20 (36v) 36 V 18-85-25 1020 35.8 38.1 29.1 22.9 2988
 2FBC25 (36v)
 39.90 30.50 23.30

N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down

2FBC20 (48v) 48 V 24-85-19 765 35.8 38.1 29.5 22.9 3120
 2FBC25 (48v)
 39.90 30.50 23.30

N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down

2FBC25E (48v) 48 V 24-85-21 850 39.8 38.1 32.6 22.9 3408
 2FBC30 (48v)
 39.90 34.40 23.30

N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down

FB16KT (36v) 36 V 18-85-17 680 23.9 38.1 20.1 22.9 2142
 40.00 20.90 24.80

N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B20 3 Wheel-Sit down Trk dims:

FB16KT (48v) 48 V 24-85-13 510 23.9 38.1 20.6 22.9 2256
 40.00 20.90 24.80

N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B20 3 Wheel-Sit down Trk dims:

FB16NT (36v) 36 V 18-85-17 680 23.9 38.1 20.1 22.9 2142
 40.00 20.90 24.80

N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B24 3 Wheel-Sit down Trk dims:

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FB16NT (48v) 40.00 20.90 24.80	48 V	24-85-13	510	23.9	38.1	20.6	22.9	2256	
N/Cov. SB350Gry Connector: 1910 Min. Weight: Term: B24 3 Wheel-Sit down Trk dims:									
FB18KT (36v) FB20KT (36v) 40.00 25.00 24.80	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 3 Wheel-Sit down Trk dims:									
FB18KT (48v) FB20KT (48v) 40.00 25.00 24.80	48 V	24-85-15	595	27.8	38.1	23.6	22.9	2568	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 3 Wheel-Sit down Trk dims:									
FB18NT (36v) FB20NT (36v) 40.00 24.90 24.80	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 3 Wheel-Sit down Trk dims:									
FB18NT (48v) FB20NT (48v) 40.00 24.90 24.80	48 V	24-85-15	595	27.8	38.1	23.6	22.9	2568	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B20 3 Wheel-Sit down Trk dims:									
FBC15(36v) FBC18(36v) 35.80 27.80 23.30	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340	
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC15(48v) FBC18(48v) 35.80 27.80 23.30	48 V	24-85-15	595	27.8	35.2	25.4	22.9	2568	
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC15K(36v) FBC18K(36v) FBC18KL(36v) 35.70 27.90 23.30	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340	
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down									

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FBC15K(48v) FBC18K(48v) FBC18KL(48v) 35.70 27.90 23.30	48 V	24-85-15	595	27.8	35.2	25.4	22.9	2568	
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC15N(36v) FBC18N(36v) FBC18LN(36v) 35.70 27.90 23.30	36 V	18-85-19	765	26.9	34.9	25.5	22.9	2340	
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC15N(48v) FBC18N(48v) FBC18LN(48v) 35.70 27.90 23.30	48 V	24-85-15	595	27.8	35.2	25.4	22.9	2568	
N/Cov. SB350Gry Connector: 1650 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC20(36/30") FBC25(36/30") 39.90 30.50 23.30	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988	
N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC20(48/30") FBC25(48/30") 39.90 30.50 23.30	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC20K (36v) 39.50 30.50 23.30	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC20K (48v) 39.50 30.50 23.30	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC20N (36v) 39.50 30.50 23.30	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FBC20N (48v) 39.50 30.50 23.30	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC25 (36/34") 39.90 34.40 23.30	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	2988	
N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC25 (48/34") 39.90 34.40 23.30	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC25E (36v) 39.90 30.50 23.30	36 V	85-25	Call for more information: (630) 851-5800						
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC25E (48v) 39.90 30.50 23.30	48 V	85-19	Call for more information: (630) 851-5800						
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC25EN(36v) FBC25LN(36v) FBC30N(36v) FBC30LN(36v) 39.50 34.40 23.30	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	2988	
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC25EN(48v) FBC25LN(48v) FBC30N(48v) FBC30LN(48v) 39.50 34.40 23.30	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC25K (36v) 39.50 30.50 23.30	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988	
N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down									

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FBC25K (48v) 39.50 30.50 23.30	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector: 2900 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC25N (36v) 39.50 30.50 23.30	36 V	18-85-25	1020	35.8	38.1	29.1	22.9	2988	
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC25N (48v) 39.50 30.50 23.30	48 V	24-85-19	765	35.8	38.1	29.5	22.9	3120	
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B24 4 Wheel-Sit down Trk dims:									
FBC30 (36v) 2FBC30 (36v) 2FBC25E (36v) 39.90 34.40 23.30	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	2988	
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC30 (48v) 39.90 34.40 23.30	48 V	24-85-23	935	Call for more information: (630) 851-5800					
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 Rider-Sit down									
FBC30K (36v) FBC25KL (36v) 2FBC25KE (36v) FBC25KE (36v) 39.50 34.40 23.30	36 V	18-85-29	1190	41.8	38.2	33.6	22.9	2988	
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC30K (48v) FBC25KL (48v) 2FBC25KE (48v) FBC25KE (48v) 39.50 34.40 23.30	48 V	24-85-21	850	39.8	38.1	32.6	22.9	3408	
N/Cov. SB350Gry Connector: 3100 Min. Weight: Term: B24 4 Wheel-Sit down									
FBC35N(36v) FBC40N(36v) 46.10 40.60 24.30	36 V	18-85-33	1360	47.7	38.3	38.2	22.9	4032	
N/Cov. SB350Gry Connector: 3400 Min. Weight: Term: B30 4 Wheel-Sit down									

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FBC35N(48v) FBC40N(48v) 46.10 40.60 24.30	48 V	24-85-29	1190	55.7	44.8	38.2	22.9	4656	
N/Cov. SB350Gry Connector: 3400 Min. Weight: Term: B30 4 Wheel-Sit down									
FBC45N(36v) 46.10 40.60 24.30	36 V	18-85-33	1360	47.7	38.3	38.2	22.9	4032	
N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 4 Wheel-Sit down									
FBC45N(48v) 46.10 40.60 24.30	48 V	24-85-29	1190	55.7	44.8	38.2	22.9	4656	
N/Cov. SB350Gry Connector: 3600 Min. Weight: Term: B30 4 Wheel-Sit down									
FBC55N(36v) 46.10 40.60 24.30	36 V	18-85-33	1360	47.7	38.3	38.2	22.9	4032	
N/Cov. SB350Gry Connector: 3975 Min. Weight: Term: B30 4 Wheel-Sit down									
FBC55N(48v) 46.10 40.60 24.30	48 V	24-85-29	1190	55.7	44.8	38.2	22.9	4656	
N/Cov. SB350Gry Connector: 3975 Min. Weight: Term: B30 4 Wheel-Sit down									
FBS15 (36v) 39.20 20.60 24.40	36 V	18-85-17	680	23.9	38.1	20.1	22.9	2142	
N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: D30 3 Wheel-Sit down Trk dims:									
FBS15 (48v) 39.20 20.60 24.40	48 V	24-85-13	510	23.9	37.8	20.4	22.9	2256	
N/Cov. SB350Gry Connector: 1900 Min. Weight: Term: D30 3 Wheel-Sit down Trk dims:									
FBS18(36v) FBS20(36v) 39.20 24.90 24.40	36 V	18-85-21	850	29.8	38.1	24.6	22.9	2556	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: D30 3 Wheel-Sit down Trk dims:									
FBS18(48v) FBS20(48v) 39.20 24.90 24.40	48 V	24-85-15	595	27.8	38.1	23.6	22.9	2568	
N/Cov. SB350Gry Connector: 2200 Min. Weight: Term: D30 3 Wheel-Sit down Trk dims:									

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh	BATTERY X in. (L)	DIMENSIONS Y in. (W)	Z in. (H)	TOTAL BATTERY WEIGHT (Lbs.)
---	------------------	-----------------	--------------------------------------	----------------------------	-------------------------------	-----------------	--------------------------------------

Class 2 Trucks

EDR 36 (21") 36 V 18-125-17 1000 35.1 38.1 20.1 30.3 2844
 ESR 36 (21")
 ESS 36 (21")
 38.62 21.25 31.62

N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: B11 Reach Trk dims:

EDR13N (24v) 24 V 12-125-17 1000 23.4 38.1 13.5 30.3 1896
 ESR15N (24v)
 ESS15N (24v)
 38.58 14.25 31.65

N/Cov. SB350Red Connector: 1600 Min. Weight: Term: B11 Reach

EDR15HN (24v) 24 V 12-125-19 1125 26.3 38.1 14.8 30.3 2136
 ESR18N (24v)
 ESR20N (24v)
 38.58 16.25 31.65

N/Cov. SB350Red Connector: 2000 Min. Weight: Term: B11 Reach Trk dims:

EOP15-24(13") 24 V 12-125-13 750 17.6 30.6 12.8 30.3 1500
 EOP15-24P(13")
 31.50 13.25 32.25

N/Cov. SB350Red Connector: 920 Min. Weight: Term: C20 Order picker Trk dims:

EOP15-24(14") 24 V 12-125-15 875 20.5 36 14 30.3 1692
 EOP15-24P(14")
 36.75 14.50 32.25

N/Cov. SB350Red Connector: 1600 Min. Weight: Term: C20 Order picker

ESR15N (36v) 36 V 18-125-11 625 21.9 38.2 13.2 30.3 1890
 EDR13N (36v)
 ESS15N (36v)
 38.58 14.25 31.65

N/Cov. 0 Connector: 1600 Min. Weight: Term: B24 Reach

ESR18N (36v) 36 V 18-125-13 750 26.3 38.2 15.4 30.3 2250
 ESR20N (36v)
 ESR20HN
 ESR23N
 38.58 16.25 31.65

N/Cov. 0 Connector: 2000 Min. Weight: Term: B24 Reach

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)		TOTAL BATTERY WEIGHT (Lbs.)
ESR23HN EDR15N EDR15HN(36v) ESS20N 38.58 16.25 31.65	36 V	18-125-13	750	26.3	38.2	15.4	30.3	2250
N/Cov. 0 Connector: 2000 Min. Weight: Term: B24 Reach								
ESS 24(16") ESR 24(16") EDR 24(16") 38.67 16.25 31.62	24 V	12-125-19	1125	26.3	38.1	14.8	30.3	2136
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach Trk dims:								
ESS 36(16") ESR 36(16") EDR 36(16") 38.67 16.25 31.62	36 V	18-125-13	750	26.3	38.2	15.4	30.3	2250
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: B11 Reach Trk dims:								
ESS-24 EDR 24 ESR 24 38.67 14.25 31.62	24 V	12-125-17	1000	23.4	38.1	13.5	30.3	1896
N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: B11 Reach								
FBC15KS (13") FBC18KS (13") 38.50 13.60 32.30	36 V	18-125-11	625	21.9	38.2	13.2	30.3	1890
N/Cov. SB350Gry Connector: 1600 Min. Weight: Term: C16 Stand up-End control								
FBC15KS (16") FBC18KS (16") 38.50 16.25 32.30	36 V	18-125-13	750	26.3	38.2	15.4	30.3	2250
N/Cov. SB350Gry Connector: 2000 Min. Weight: Term: C16 Stand up-End control								
FBC15KS (18") FBC18KS (18") 38.50 18.50 32.30	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538
N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: C16 Stand up-End control Trk dims:								

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
FBC15KS (21") FBC18KS (21") 38.50 21.25 32.30	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: C16 Stand up-End control Trk dims:									
FBC20KS (18") 38.50 18.50 32.30	36 V	18-125-15	875	30.7	38.1	17.7	30.3	2538	
N/Cov. SB350Gry Connector: 2300 Min. Weight: Term: C16 Stand up-End control Trk dims:									
FBC20KS (21") 38.50 21.25 32.30	36 V	18-125-17	1000	35.1	38.1	20.1	30.3	2844	
N/Cov. SB350Gry Connector: 2600 Min. Weight: Term: C16 Stand up-End control Trk dims:									
FBC25KS 38.50 23.75 32.30	36 V	18-125-19	1125	39.5	38.2	22.4	30.3	3204	
N/Cov. SB350Gry Connector: 2700 Min. Weight: Term: C16 Stand up-End control Trk dims:									
Class 3 Trucks									
PMCR30 PMCR40 31.50 13.44 24.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 825 Min. Weight: Term: B18 Pallet-Walk/ride Trk dims:									
PMT 90 31.50 13.44 24.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 825 Min. Weight: Term: B18 Pallet-Walk/ride Trk dims:									
PMW 20 29.38 8.88 26.50	24 V	12-85-7	255	6	25.4	8.6	23.3	708	
W/Cov. SB175Gry Connector: 200 Min. Weight: Term: B12 Pallet-Walkie Trk dims:									
PMW 30 (9") 31.50 9.20 24.00	24 V	12-85-7	255	6	25.4	8.6	23.3	708	
W/Cov. SB175Gry Connector: 575 Min. Weight: Term: B18 Pallet-Walkie Trk dims:									
PMW23N 25.00 8.86 23.23	24 V	12-85-5	170	4	24.9	7.8	22.9	576	
N/Cov. SB175Gry Connector: 0 Min. Weight: Term: 00 Pallet-Hand trucks Trk dims:									

Mitsubishi Forklift Model # Battery Compartment Size	V O L T	BATTERY TYPE	CAPACITY 6 HOUR RATE Ah kWh		BATTERY X in. (L)	DIMENSIONS Y in. (W) Z in. (H)			TOTAL BATTERY WEIGHT (Lbs.)
PMW23NL 31.26 8.70 26.02	24 V	12-85-7	255	6	25.4	8.6	23.3	708	
W/Cov. SB175Gry Connector: 220 Min. Weight: Term: A18 Pallet-Walkie Trk dims:									
PMW30(13") 31.50 13.44 24.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 575 Min. Weight: Term: B18 Pallet-Walkie Trk dims:									
PMW30N 24.43 11.00 25.10	24 V	12-85-7	255	Call for more information: (630) 851-5800					
N/Cov. SB175Gry Connector: 0 Min. Weight: Term: 00 Pallet-Hand trucks Trk dims:									
PMW30NL 31.97 13.58 30.98	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 220 Min. Weight: Term: B18 Pallet-Rider/Walkie Trk dims:									
PMWR30 PMWR40 31.50 13.44 24.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov. SB175Gry Connector: 825 Min. Weight: Term: B18 Pallet-Walk/ride Trk dims:									
PMWR30N PMWR40N 31.97 13.46 30.98	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
W/Cov. SBX350Red Connector: 933 Min. Weight: Term: A18 Pallet-Rider/Walkie Trk dims:									
PMWS15 PMWT15 PMWT20 31.90 13.44 24.00	24 V	12-85-13	510	11.9	30.6	12.8	23.3	1128	
N/Cov. 0 Connector: 925 Min. Weight: Term: 00 Pallet-Walk/ride Trk dims:									